



## Daylight Fresnel 1.8kW/1.2kW SE

### LAMPHEAD CONTENTS

- Lamp Housing without Bulb (purple grey & silver color)
- 4-leaf Rotatable Barndoor with Safety Wire
- Ø175mm (6-7/8 in.) Fresnel Lens
- Inlet Cable with Multi-Pin Connector
- Stirrup with Ø28mm (1-1/8 in.) Spigot

# Requires Electronic Ballast, Lamphead to Ballast Cable and Lamp Bulb

## Daylight Fresnel 1.8kW/1.2kW SE

### SPECIFICATIONS

Identity No.	L01812DS
Capacity	1,800W / 1,200W
Lamp Bulb Voltage	140V / 100V
Fresnel Lens	Ø175mm (6-7/8 in.)
Lamp Type	CSR 1800/SE/HR or HMI 1800W/SE MSR 1200/HR or HMI 1200W/SE
Color Temp.	5600K
Lamp Holder	G38
Stirrup	Ø28mm (1-1/8 in.) Spigot
Class / IP Rating	1 / IP 23
Max. Surface Temp.	180 °C / 170 °C
Max. Ambient Temp.	45 °C
Min. Distance to Illuminated Object	6 m
Min. Distance to Flammable Object	0.5 m
Operating Range	+45° ~ 0° ~ -45°
Weight (lamphead)	9.7 kg
Weight (with barndoor)	10.7 kg

### ACCESSORIES

Electronic Ballast V3 : 1.8kW/1.2kW/575W

Lamphead to Ballast Cable : 7m (23 ft.) or 15m (49 ft.)

4-leaf Rotatable Barndoor

Filter Frame

Set of 4 Scrims Ø229mm (9 in.) :


Full Single, Full Double, Half Single, Half Double

Scrim Bag


Safety Cable (for lamphead)

Safety Wire (for barndoor)

### PHOTOMETRIC DATA



1800W			
Spot (5°)			
Lux	90000	20000	9000
Beam Ø	0.26 m	0.52 m	0.79 m
Flood (52°)			
Lux	1200	3200	1500
Beam Ø	2.93 m	5.85 m	8.78 m



1200W			
Spot (5°)			
Lux	102403	25601	11378
Beam Ø	0.26 m	0.52 m	0.79 m
Flood (52°)			
Lux	7799	1950	867
Beam Ø	2.93 m	5.85 m	8.78 m

### DIMENSIONS (mm)

